

# SCIENTIFIC REPORTS

OPEN

## Erratum: Bona-fide method for the determination of short range order and transport properties in a ferro-aluminosilicate slag

Konstantinos T. Karalis, Dimitrios Dellis, Georgios S. E. Antipas & Anthimos Xenidis

*Scientific Reports* 6:30216; doi: 10.1038/srep30216; published online 26 July 2016; updated on 27 September 2016

In this Article, the rows in Table 3 are misaligned. The correct Table 3 appears below

		Temperature (K)						
		1273.15	1473.15	1673.15	1773.15	1873.15	2073.15	2273.15
	CN	% of feature						
Si-O	3	0.10	—	0.10	0.30	0.30	—	0.52
	4	99.58	99.06	98.74	98.74	97.70	96.97	97.70
	5	0.20	0.80	1.14	0.80	1.67	2.40	1.67
Al-O	2	—	—	—	—	—	1.74	2.32
	3	—	8.72	7.55	4.65	9.88	16.27	27.90
	4	43.02	70.34	65.11	65.11	57.55	68.02	58.72
	5	49.41	18.60	23.83	16.16	27.90	12.79	9.88
	6	7.55	1.74	3.48	2.90	2.90	0.58	0.58
Fe-O	1	—	—	—	—	—	—	1.95
	2	1.69	2.21	2.73	4.55	5.591	6.63	19.63
	3	15.99	21.84	27.82	30.68	32.25	34.33	48.24
	4	56.17	53.44	54.74	51.23	49.28	46.16	28.21
	5	23.53	21.06	14.43	12.35	11.83	11.44	1.82
	6	2.60	1.43	—	0.52	—	—	—

**Table 3.**



This work is licensed under a Creative Commons Attribution 4.0 International License. The images or other third party material in this article are included in the article's Creative Commons license, unless indicated otherwise in the credit line; if the material is not included under the Creative Commons license, users will need to obtain permission from the license holder to reproduce the material. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0/>

© The Author(s) 2016